

Type 1.2 Specification Sheet

Compact BMU on a vertical track system along a roof parapet

The Manntech™ Type 1.2 track-based compact building maintenance unit has the track system anchored to the roof parapet. Suitable for use on buildings with a load-bearing parapet. Preferred application for buildings with non-load-bearing roofs and/or insufficient space on the roof. Also suitable for use on buildings with extremely high parapets.



Type 1.2 in parked position with covered work platform

Key Features

- Automation ready, fully digital BMU
- Lowest life-cycle costs and maximum availability due to predictive maintenance systems
- Remote monitoring for convenient building management
- Control system with the highest safety level worldwide
- Safe and efficient operation also on very narrow passageways

Specifications

Hoist mechanism	EN 1808 Manntech 4-rope multi-position safety
Rated working load (standard)	240-500 kgs
Height coverage (standard)	125-270m
Rope diameter	7-10mm
Rope safety factor according to EN 1808	>12
Lifting speed	~11m/min
Traversing speed	~10-15m/min
Power cable	Optional
Cradle	+/- 45° Slewing function of cradle (optional)

MANNTECH and related logos are registered trademarks of Alimak Group AB (publ) and its subsidiaries ("Alimak Group"), in several jurisdictions, including but not limited to the EU and the United States. Alimak Group retains all rights in its name and for above mentioned trademarks, whether registered or not.